

Vacuum Atmosphere Furnace



Furnace and heating process equipment widely using at Institutions of higher learning scientific research institutions experimental laboratory industrial and mining enterprises, etc.

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

Vacuum atmosphere Lift Furnace

(Furnace inside with agitation)

GWL-VSF-SR



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Lift Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-VSF-SR				
Working Temperature	1200℃	1400℃	1600℃	1700℃	1800℃
Maximum Temperature	1250℃	1450℃	1650℃	1750℃	1820℃
Heating Element	U Type Silicon Carbide Rod		U Type Silicon molybdenum rod		
Diameter Of Furnace Hearth	200 mm 300mm 500mm 800mm				
Height Of Furnace Hearth	300mm 500mm 800mm 1000mm				
Lift Method	Screw Mandrel				
Temperature Rise Rate	Temperature Rise Rate Can Be Modify（30℃/min 1℃/company Suggest 10-20℃/min.				
Vacuum Degree	-0.1Mpa（Can Customize As 1Pa, -1Pa, -0.01Pa and so on）				
Rated Voltage	380V				
Temperature Uniformity	±1℃				
Temperature Control Accuracy	±1℃				
Furnace Lining Materials	High Purity Alumina Fiber Board	Import Morgan Light Material	Import High Purity Morgan Light Material		
Rotation Speed	1-50r/min				
Standard Accessories	Heating Elements 2 Pieces, Specification Certificate, One Piece Heat Insulation Brick, A Pair Crucible Pliers, One Pair Of High Temperature Gloves. One-piece special crucible for tube furnace, Two-piece seal rings				
Characteristic: Furnace hearth with agitation; High Temperature uniformity. 1. Temperature accuracy: ±1℃ ; Constant temperature: ±1℃(Base on Heating zone size) 。 2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling, unattended operation 3. Cooling structure: Double layer furnace shell, air cooling and water cooling 4. Furnace surface temperature approach the indoor temperature. 5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on) 6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold 7. More gas options（Oxygen、Nitrogen、Argon、hydrogen and so on） Furnace Hearth And Atmosphere Can Be Customized					

Vacuum Atmosphere Chamber Furnace

GWL-ZQLB



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Chamber Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-ZQLB			
Working Temperature	1200℃	1400℃	1600℃	1700℃
Maximum Temperature	1250℃	1450℃	1650℃	1750℃
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod	
Dimension Of Furnace Hearth	200*150*150 300*200*200 400*200*200 500*300*200 500*300*300 600*400*400 800*500*500 1000×700×600			
Vacuum Degree	-0.1MPa			
Temperature Rise Rate	Temperature Rise Rate Can Be Modify（30℃/min 1℃/h）, Company Suggest 10-20℃/min.			
Pressure Protection	The system is specially made to prevent the danger of closure of the exhaust port, the blockage of the exhaust port and the excessive pressure of the furnace tube. The signal is obtained by the electric contact pressure meter or pressure sensor then the drive control module will close the electromagnetic inlet valve and starts the electromagnetic exhaust valve and the alarm. to ensure the furnace can be used properly and safely.			
Rated Voltage	380V			
Temperature Uniformity	±1℃			
Temperature Control Accuracy	±1℃			
Furnace Lining Materials	High purity alumina fiber board	Import Morgan Material	Import High Purity Morgan Material	
Vacuum Pump	Double stage direct rotary vane vacuum pump			
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloves.			
Characteristic: Operational simplicity, No need Working Table, Water + air cooling. 1. Temperature accuracy: ±1℃ ; Constant temperature: ±1℃(Base on Heating zone size) 。 2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling, unattended operation 3. Cooling structure: Double layer furnace shell, air cooling and water cooling 4. Furnace surface temperature approach the indoor temperature. 5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on) 6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold 7. More gas options（Oxygen、Nitrogen、Argon、hydrogen and so on） Furnace Hearth And Atmosphere Can Be Customized				

Vacuum Atmosphere Chamber Furnace (Corrosion Resistance Without Water Cooling) GWL-ZQLB



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Chamber Furnace (Corrosion Resistance Without Water Cooling)

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-ZQLB	
Working Temperature	1200 °C	1400°C
Maximum Temperature	1250 °C	1450°C
Heating Element	Silicon Carbide Rod	
Dimension Of Furnace Hearth	200*150*150 300*200*200 400*200*200 500*300*200 500*300*300 600*400*400 800*500*500 1000×700×600	
Vacuum Degree	-0.1MPa	
Temperature Rise Rate	Temperature Rise Rate Can Be Modify (30°C/min 1°C/h) , Company Suggest 10-20°C/min.	
Pressure Protection	The system is specially made to prevent the danger of closure of the exhaust port, the blockage of the exhaust port and the excessive pressure of the furnace tube. The signal is obtained by the electric contact pressure meter or pressure sensor then the drive control module will close the electromagnetic inlet valve and starts the electromagnetic exhaust valve and the alarm. to ensure the furnace can be used properly and safely.	
Rated Voltage	380V	
Temperature Uniformity	±1°C	
Temperature Control Accuracy	±1°C	
Furnace Lining Materials	Alumina Polymer Light Material	
Vacuum Pump	Double stage direct rotary vane vacuum pump	
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloves.	
Characteristic: Operational simplicity, No need Working Table, Corrosion Resistance. <div>1. Temperature accuracy: ±1°C ; Constant temperature: ±1°C(Base on Heating zone size) 。 2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling, unattended operation 3. Cooling structure: Increase the thickness of insulation layer, without water cooling 4. Furnace surface temperature approach the indoor temperature. 5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on) 6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold 7. More gas options (Oxygen、Nitrogen、Argon、hydrogen and so on)</div>		
Furnace Hearth And Atmosphere Can Be Customized		

Vacuum Atmosphere Pit Furnace

GWL-ZQJ



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Pit Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-ZQJ				
Working Temperature	1200 °C	1400 °C	1600 °C	1700 °C	1800 °C
Maximum Temperature	1250 °C	1450 °C	1650 °C	1750 °C	1820 °C
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod		
Diameter Of Furnace Hearth	200MM 300MM 500MM 600MM				
Height of furnace hearth	300MM 500MM 800MM 1000MM				
Vacuum Degree	-0.1MPa				
Temperature Rise Rate	Temperature Rise Rate Can Be Modify（30°C/min 1°C/h），Company Suggest 10-20°C/min.				
Pressure Protection	The system is specially made to prevent the danger of closure of the exhaust port, the blockage of the exhaust port and the excessive pressure of the furnace tube. The signal is obtained by the electric contact pressure meter or pressure sensor then the drive control module will close the electromagnetic inlet valve and starts the electromagnetic exhaust valve and the alarm. to ensure the furnace can be used properly and safely.				
Rated Voltage	380V				
Temperature Uniformity	±1°C				
Temperature Control Accuracy	±1°C				
Furnace Inner Tank Materials	Sealed with the stainless steel 310S Material (Vary according furnace temperature) Can be removable under high temperature environment.				
Furnace Lining Materials	Alumina Polymer Light Material				
Vacuum Pump	Double stage direct rotary vane vacuum pump				
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloyes.				
Characteristic: Operational Simplicity, Less land occupation, Top open. <div><div>1.</div><div>Temperature accuracy: ±1°C; Constant temperature: ±1°C(Base on Heating zone size) 。</div></div> <div><div>2.</div><div>Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining, automatic cooling,unattended operation</div></div> <div><div>3.</div><div>Cooling structure: Air + Water Cooling.</div></div> <div><div>4.</div><div>Furnace surface temperature approach the indoor temperature.</div></div> <div><div>5.</div><div>double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on)</div></div> <div><div>6.</div><div>Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold</div></div> <div><div>7.</div><div>More gas options（Oxygen、Nitrogen、Argon、hydrogen and so on）</div></div>					
Furnace Hearth And Atmosphere Can Be Customized					

Vacuum Atmosphere Hot Press Furnace

GWL-VSF-RY



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Hot Press Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature

of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters

and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-VSF-RY		
Working Temperature	1200 °C	1400 °C	1600°C
Maximum Temperature	1250 °C	1450 °C	1650°C
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod
Diameter Of Furnace Hearth	200MM 300MM 500MM 600MM		
Height of furnace hearth	300MM 500MM 800MM 1000MM		
Vacuum Degree	-0.1MPa(Can Customize As 1Pa, -1Pa, -0.01Pa and so on)		
Temperature Rise Rate	Temperature Rise Rate Can Be Modify (30°C/min 1°C/h) , Company Suggest 10-20°C/min.		
Pressure	0.5 Ton to 150 Ton (Can be customize)		
Pressure mechanical	Electric precision hydraulic press		
Pressure adjustment	Digital display manual adjustment		
Pressure Display	Digital display, Unit (N)		
Pressure Constant	Equipped with imported electromagnetic valve, excellent pressure constant state		
Record Of Pressure, Temperature Change	Paper printer		
Pressure Protection	The system is specially made to prevent the danger of closure of the exhaust port, the blockage of the exhaust port and the excessive pressure of the furnace tube. The signal is obtained by the electric contact pressure meter or pressure sensor then the drive control module will close the electromagnetic inlet valve and starts the electromagnetic exhaust valve and the alarm. to ensure the furnace can be used properly and safely.		
Rated Voltage	380V		
Temperature Uniformity	±1°C		
Temperature Control Accuracy	±1°C		
Furnace Lining Materials	Alumina polymer light material		
Vacuum Pump	Double stage direct rotary vane vacuum pump		
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloves.		
Characteristic: Operational Simplicity, Excellent Temperature Accuracy. 1. Temperature accuracy: ±1°C ; Constant temperature: ±1°C(Base on Heating zone size) 。 2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling,unattended operation 3. Cooling structure: Air + Water Cooling. 4. Furnace surface temperature approach the indoor temperature. 5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supplyprotection and so on) 6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold 7. More gas options (Oxygen、Nitrogen、Argon、hydrogen and so on)			
Furnace Hearth, Atmosphere And Pressure Can Be Customized			

Vacuum Atmosphere Lift Furnace

GWL-ZKSS



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Lift Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature

of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters

and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



HLQ Induction Equipment Co., Ltd

Model	GWL-ZKSS				
Working Temperature	1200℃	1400℃	1600℃	1700℃	1800℃
Maximum Temperature	1250℃	1450℃	1650℃	1750℃	1820℃
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod		
Dimension Of Furnace Hearth	800*500*500 MM 800*800*800 MM 1300*600*600 MM 1300*750*600 MM 1500*800*800 MM				
Loading Platform Lift Method	Screw Mandrel Lift (Lifting speed adjustable)				
Vacuum Degree	-0.1MPa				
Temperature Rise Rate	Temperature Rise Rate Can Be Modify（30℃/min 1℃/h）, Company Suggest 10-20℃/min.				
Water cooling	Equip circulating water pump and tank				
Refractories Of Loading Platform	Vacuum forming high purity alumina light material and hollow ball material, to ensure the heat preservation and bearing capacity				
Loading platform passes in and out	Electric screw mechanical drive(Pass in and out speed adjustable)				
Protection	The system is specially made to prevent the danger of closure of the exhaust port, the blockage of the exhaust port and the excessive pressure of the furnace tube. The signal is obtained by the electric contact pressure meter or pressure sensor then the drive control module will close the electromagnetic inlet valve and starts the electromagnetic exhaust valve and the alarm. to ensure the furnace can be used properly and safely.				
Rated Voltage	380V				
Temperature Uniformity	±1℃				
Temperature Control Accuracy	±1℃				
Furnace Lining Materials	Alumina polymer light material				
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloves.				

Characteristic:

Operational Simplicity, Screw mandrel lift, Excellent precision.

1. Temperature accuracy: ±1°C ; Constant temperature: ±1°C(Base on Heating zone size) 。
2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling, unattended operation
3. Cooling structure: Air + Water Cooling.
4. Furnace surface temperature approach the indoor temperature.
5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on)
6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold
7. More gas options (Oxygen、Nitrogen、Argon、hydrogen and so on)
8. 2 of Loading Platforms Can be customized. (More efficient and energy-efficient)

Furnace Hearth, Vacuum Degree Can Be Customized

High Vacuum Atmosphere Sintering Furnace

GWL-GZK



GWL Series 1200°C-1800°C High Vacuum Atmosphere Sintering Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-GZK			
Working Temperature	1200 °C	1400 °C	1600°C	1700 °C
Maximum Temperature	1250 °C	1450 °C	1650°C	1750 °C
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod	
Dimension Of Furnace Hearth	200*150*150 MM 300*200*200 MM 400*200*200 MM 500*300*200 MM 500*300*300 MM			
Vacuum Degree	-0.1MPa			
Temperature Rise Rate	Temperature Rise Rate Can Be Modify（30°C/min 1°C/h）, Company Suggest 10-20°C/min.			
Water cooling	Equip circulating water pump and tank /（300L）			
Rated Voltage	380V			
Temperature Uniformity	±1°C			
Temperature Control Accuracy	±1°C			
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloves.			
Characteristic: Operational Simplicity, High Vacuum Degree, Excellent Sealing Performance. 1. Temperature accuracy: ±1°C ; Constant temperature: ±1°C(Base on Heating zone size) 。 2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling, unattended operation 3. Cooling structure: Air + Water Cooling. 4. Furnace surface temperature approach the indoor temperature. 5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on) 6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold 7. More gas options（Oxygen、Nitrogen、Argon、hydrogen and so on） 8. Furnace lining materials: 1200°C: High purity alumina fiber board; 1400°C: High purity alumina contains zirconium fiber board; 1600°C:Import highpurity alumina fiber board; 1700°C: Imported German MESCHUPP vacuum forming high purity alumina poly light material.				
Furnace Hearth, Vacuum Degree Can Be Customized				

High Temperature Vacuum Atmosphere Lift Furnace (Screw Mandrel) GWL-ZQSS



GWL Series 1200°C-1800°C High Temperature Vacuum Atmosphere Lifting Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port /Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$. Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-ZQSS				
Working Temperature	1200°C	1400°C	1600°C	1700°C	1800°C
Maximum Temperature	1250°C	1450°C	1650°C	1750°C	1820°C
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod		
Dimension Of Furnace Hearth	200*150*150 MM 300*200*200 MM 400*200*200 MM 500*300*200 MM 500*300*300 MM				
Vacuum Degree	-0.1MPa				
Temperature Rise Rate	Temperature Rise Rate Can Be Modify（30°C/min 1°C/h）, Company Suggest 10-20°C/min.				
Water cooling	Equip circulating water pump and tank（300L）				
Loading Platform Lift Method	Screw Mandrel Lift (Lifting speed adjustable)				
Loading platform passes in and out	Hydraulic / Mechanical				
Loading Capacity	1-3 Ton				
Rated Voltage	380V				
Temperature Uniformity	±1°C				
Temperature Control Accuracy	±1°C				
Standard Accessories	Heating Elements, Specification Certificate, Heat Insulation Brick, Crucible Pliers, High Temperature Gloves.				

Characteristic:

Operational Simplicity, Screw mandrel lift, Excellent precision.

1. Temperature accuracy: $\pm 1^{\circ}\text{C}$; Constant temperature: $\pm 1^{\circ}\text{C}$ (Base on Heating zone size) 。
2. Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining , automatic cooling, unattended operation
3. Cooling structure: Air + Water Cooling.
4. Furnace surface temperature approach the indoor temperature.
5. double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on)
6. Importing refractory, excellent temperature retaining effect, high temperature resistance, Tolerance the extreme heat and cold
7. More gas options (Oxygen、Nitrogen、Argon、hydrogen and so on)
8. Furnace lining materials: 1200°C: High purity alumina fiber board; 1400°C: High purity alumina contains zirconium fiber board; 1600°C: Import highpurity alumina fiber board; 1700-1800°C: Imported German MESCHUPP vacuum forming high purity alumina poly light material.
9. 2 of Loading Platforms Can be customized. (More efficient and energy-efficient)

Furnace Hearth, Vacuum Degree, And Lift Method Can Be Customized